


แหวนกดล้อ

ว 10

CIRCULAR EXTERNAL NUTS

แหวนกดล้อ

CIRCULAR EXTERNAL NUTS



มาตรฐาน -

วัตถุดิบ เหล็ก

ชุบผิว ชุบดำ

รหัสสินค้า แหวนกดล้อ 03-034

ขนาด	Ring Dimension				Application shaft			Thrust	☒ AVAILABLE SIZE	
	d1		d3		t	No. of	S	Load		
	Basic	Tol.	Basic	Tol.		Teeth	Basic	Tol	kgf	
CSTW – 2	1.9	n 0.05	6	n0.2	0.25	3	2	+0.03	6	☒
CSTW – 2.5	2.2	+0.1	6.4	n0.2	0.25	3	2.4	n0.03	6	☒
CSTW – 3	2.8	0	8	n0.2	0.25	4	3	n0.03	9	☒
CSTW – 3.5	3.3	−0.1	7.5	n0.2	0.25	4	3.5	n0.03	10	☒
CSTW – 4	3.8	+0.1	9	n0.2	0.25	4	4	n0.03	12	☒
CSTW – 5	4.8	+0.1	10	n0.2	0.25	5	5	n0.03	16	☒
CSTW – 6	5.8	+0.1	11	n0.2	0.25	5	6	n0.03	18	☒
CSTW – 8	7.8	+0.1	13	n0.2	0.25	5	8	n0.03	21	☒
CSTW – 10	9.8	+0.1	15.4	n0.2	0.25	6	10	n0.03	21	☒
CSTW – 12	11.8	+0.1	17.8	n0.3	0.4	6	12	n0.03	23	☒
CSTW – 14	13.8	+0.1	20.3	n0.3	0.4	6	14	n0.03	23	☒
CSTW – 16	15.8	+0.1	22.8	n0.3	0.4	6	16	n0.05	23	☒